



#	Product Number	Product Name	M.F.H.	Count
A	NRO213-xx01	Park Bench with Backrest	0'-0"	5
B	NRO930307-US	Robinia Funpoint	0'-0"	1
C	COR104301-xx03	Treasure Island	7'-5"	1
D	NRO926-CUSTOM_20327590	3-Bay Swing	7'-11"	1
E	NRO816-xx03	Six-Sided Climbing Structure	9'-2"	1
F	NRO893094-US	Balance Net	1'-4"	1
G	MOM162909_ASTM_FD	Insect Seesaw	3'-3"	1
H	NRO933510-ASTM	4-Foot Balance Beam	1'-0"	1
I	GYX958000-xx17	Saturn 4 Carousel	7'-1"	1
J	PCM52831-xx01	Hideaway Tree	6'-8"	1
K	NRO822-0603	Waterlilies Balance Post	1'-1"	2
L	PCMS727546-ASTM	Tree Themed ADA Monkey Bars	4'-6"	1
M	NRO931647-ASTM	Infant Swing - 1-Bay	3'-10"	1
N	NRO989495-US	Crawl Tunnel	3'-11"	1
O	NRO933509-ASTM	6-Foot Balance Beam	1'-0"	1
P	NRO930243-US	Mini-Suspension Bridge	1'-7"	1
Q	PCM52431-xx01	Ice Cream Cart	0'-0"	1
R	NRO815-xx01	Hammock	4'-2"	1
S	NRO894983-US	Storytelling Circle W/ Throne	0'-0"	1
T	NRO212-xx01	Kids Table with 4 Sitting Poles	0'-0"	2
U	NRO510-xx01	Sand Desk	0'-0"	1
V	KRS820022A	Owl Sculpture	9'-4"	1
X	KRS8200872	Nest Log Jumble	3'-7"	1
Y	KRS8200603	Egg Playhouse	0'-0"	1
Z	NRO501-Xx01	7ft EWF Edge	0'-0"	80
AA	NRO217-Xx01	2-5 Age Robinia Sign	0'-0"	1
BB	NRO217 CUSTOM_20342526	5-12 Age Robinia Sign	0'-0"	1

MAINTENANCE OF ASTM F1951 COMPLIANT LOOSE FILL SURFACING IS THE RESPONSIBILITY OF THE SITE OWNER TO ENSURE ADA REQUIREMENTS FOR PATH OF TRAVEL.

ADA ACCESSIBLE PATH TO SITE IS REQUIRED, PER 2010 ADA STANDARDS (SECTION 206)

TATLOCK SPORTS COMPLEX

80 Butler Pkwy
Summit, NJ
Site Plan - Option 1



1/32"=1'-0" ON 11" x 17" SHEET

MANUFACTURER'S SHOP DRAWING:

FOR USE BY CONTRACTOR, ENGINEER, OR DESIGN PROFESSIONAL OF RECORD. SEE SIGNED SALES PROPOSAL FOR COMPLETE SCOPE TO BE PROVIDED BY KOMPAN OR REPRESENTING AGENCY. CONFIRM FINAL PLAN AND SCOPE WITH KOMPAN SALES REP OR PROJECT MANAGER PRIOR TO USE FOR REVIEW, PERMITTING, OR CONSTRUCTION.

TO BE READ CONTINGENTLY WITH KOMPAN'S STANDARDS FOR SITE PREPARATION, MATERIALS AND INSTALLATION PROCESSES. PROVIDED AFTER EQUIPMENT PURCHASE, A COMPLIANT PLAYGROUND TO KOMPAN'S STANDARDS MUST SATISFY ALL REQUIREMENTS IN THE CODE OF CONDUCT.

SLAB BY OTHERS UNLESS OTHERWISE NOTED. FOR SURFACE MOUNT OPTIONS, THE CONCRETE REQUIREMENTS MAY BE UP TO 5/8" OF 3,500 PSI MINIMUM COMPRESSIVE STRENGTH. CONTACT KOMPAN FOR SPECIFIC PRODUCT REQUIREMENTS. ALL COMPOSITE STRUCTURES SHOWN REQUIRE A SITE GRADE OF 2% MAXIMUM, 1% OPTIMAL. SPECIFICATIONS FOR EACH KOMPAN STRUCTURE MAY BE FOUND AT KOMPAN.COM/KOMPANMASTER

DIMENSIONS OF PLAY AREA, SIZE AND ORIENTATION, LOCATIONS OF ALL EXISTING UTILITIES, EQUIPMENT AND SITE FURNISHINGS TO BE FIELD VERIFIED PRIOR TO CONSTRUCTION.

PREPARED AND PRINTED IN USA BY KOMPAN © 2025 KOMPAN, INC. AUSTIN, TX. USA 800-426-9788



KOMPAN
Let's play

SALES REPRESENTATIVE		SHEET
EnKy		K1.1
REVIEW BY DESIGN	DRAWN BY TifTib	DATE 01/06/2025
REV. NO. 1	REV. BY TifTib	REV. DATE 02/04/2025
		REVISION NOTES Updated Equip IDs

LAYOUT IS IN ACCORDANCE WITH ASTM F1487